

IMPORTANT: Please completely understand all user instructions and safety information before using this product.

TOOLS REQUIRED

4mm Allen wrench
8mm Open-ended wrench
Torque Wrench



NOTE

The **GORILLA XT** cage comes loosely attached to the **DELTA** mount with 22mm long screws. This **DELTA** has a 3/8" black cylindrical spacer on the top screw and 1/4" black cylindrical spacer on the bottom screw. The spacers are to ensure that even with long saddles like the Fi'zi:k, the water bottle will clear the rear of the saddle. There are also two silver 1/8" spacers beneath the locking nuts, to allow easy access to the nuts with an 8mm wrench. The mount is attached loosely to its backplate with two 15mm long screws with red Loctite on the threads that will help prevent the screws loosening once installed on the saddle.

INSTALLATION INSTRUCTIONS

HELPFUL HINT: The spacing of the rear saddle rails varies from each manufacturer. With some saddles it may be necessary to invert the Back Plate and have the narrowest part of the plate up under the saddle. This may allow easier access to the two threaded mounting holes.

STEPS

1. Using a 4mm Allen wrench and an 8mm wrench, fully tighten the two 22mm long screws holding the cage to the mount. Tighten to 30 in.lbs (3.4 nm) of torque.
2. Next unscrew the two 15mm screws from the backplate.
3. Hold the mount up to the back of the saddle rails and position the backplate inside the rails.
4. Insert the two 15mm screws through the mount into the backplate. Hand-tighten and then check that the cage is in the position you require. Tighten to 30 in.lbs (3.4 nm) of torque **DO NOT EXCEED THIS TORQUE**. The Loctite on the threads will harden over 24 hours. You can still remove the screws in the future but the Loctite is a one-time use. You can purchase replacement screws with Loctite on the XLAB web store.
5. To add the recommended XLAB X-STRIKE CO₂ Inflation Kit between the cage and the black spacers, you will need to replace the two 22mm screws with the two long 30mm screws included with these instructions. Tighten to 30 in.lbs (3.4 nm) of torque.

MAINTENANCE

As with any high-tech racing gear, you need to routinely check for loose hardware, cracks or other damage and replace as required.

WARRANTY

2 Year warranty on **DELTA** mount. Lifetime warranty on **GORILLA XT** cage. See website for details